


# IBOX-602-5C3L-2P




- 9th/8th/7th/6th Gen Intel® Core™ i7/i5/i3 (Skylake, Kaby Lake and Coffee Lake) with Desktop-grade Intel® Z370 chipset, support processor up to 65W TDP;
- Up to 4 front-access 2.5" SSD trays, RAID 0, 1, 5 supported, besides that, it support working with up two 3\* PCIe/PCI slot;
- 2\* M.2 sockets, 1\* M.2 Key M, 1\* M.2 Key E for SSD and WiFi, 1\* Mini PCIe slot comes with SIM card slot support 4G LTE Module;
- IBOX-602-5C3L series is offering 4\* isolated serial port supporting RS232/485 switchable by internal jumper;
- 9V to 36V DC Power Input with Surge Protection, configurable Ignition Power Control;
- Fully enclosed full aluminum alloy with fanless cooling system offering anti-interference structure and stable system with Modular parts cable-free design for better vibration resistance.





## Specifications

The actual appearance is subject to the final configuration.

<b>Model</b>	IBOX-602-5C3L-2P			
<b>Supported OS</b>	Win 7, Win 8, Win 10, Win 11, Linux (Ubuntu, Debian, Kali, CentOS, etc.); WES 7; Win 10 IoT			
<b>Chipset</b>	Intel® Z370 Chipset			
<b>CPU</b>	Processor Socket	Intel® Desktop Processors Socket LGA1151		
	Series	6th Gen. Intel® Core™ Processor	Intel® Celeron® G4900 Processor	7th-9th Gen. Intel® Core™ Processor
	TDP	Up to 65W	54W	Up to 65W
	Graphic	Intel® HD Graphics 530	Intel® UHD Graphics 610	7th Gen. Intel® HD Graphics 630 8th/ 9th Gen. Intel® UHD Graphics 630
<b>RAM</b>	Type&Qty	2* SO-DIMM Socket	2* SO-DIMM Socket	2* SO-DIMM Socket
	Frequency	DDR4-1866/2133 MHz	DDR4-2400 MHz	DDR4-2400/2666 MHz
	Capacity	Up to 32GB	Up to 32GB	Up to 32GB
<b>Storage Device</b>	SATA	1* 2.5" SATA3.0 Bay on board (6Gb/s); 3* SATA3.0 connectors (6Gb/s), Support RAID (0/1/5)		
	MSATA	1* mSATA3.0 slot on board (6Gb/s)		
	M.2	1* M.2 (NGFF) 2280 M-key slot, support PCIe4 Gen.3 NVMe/ SATA3.0 SSD		
<b>I/O Interface</b>	COM	4* Isolated DB9 COM Ports with ESD/EFT/Surge protection (COM1-4, support RS232/485, switchable by jumper); 1* RS232 with DB9 connector (COM5); 1* RS232 header (COM6)		
	Ethernet	3* Intel® i211 GbE LAN, RJ45 connector		
	USB	8* USB 3.0; 2* USB2.0; 1* Internal USB2.0		
	Video	1* HDMI, Support 4096x2304@24Hz, (Optional 1* DP, Support 4096 x 2304@60Hz); 1* VGA, Support 1920x1200@60Hz;		
	Audio	1* MIC, 1* SPK; With 5.1 channels HD Audio Codec Realtek ALC662		
	SIM	1* External SIM card slot connected to Mini-PCIe		
	Power Supply	9V-36V DC; 1* 4-Pin DC Power Jack (Circular DIN Connectors, Full-Shield, optional with Phoenix Terminal Connector)		
	Other	1* 8-bit GPIO, Terminal Block (12-Pin, 3.81mm), 4-Inputs/4-Outputs, 0-5V Input Range 1* Terminal Block (4-Pin, 3.81mm Pitch) with Remote Switch and Power Indicator 1* PS/2 for keyboard/ mouse; 1* Auto-On Switch; 1* TPM header (2*10-pin)		
<b>Extended Capabilities</b>	Additional Internal Interface	1* PCIe x4+1* PCIe x16 or 1* PCI+1* PCIe x4 or 2* PCI or 1* PCIe x1+1* PCIe x4 or 1* PCI+1* PCIe x16; (PCIe Gen.3) 1* Full Size Mini-PCIe with SIM card slot; (PCIe+USB2.0); 1* M.2 2230 E-key Slot (PCIe+USB2.0, support WiFi+BT)		
<b>Environment</b>	Operating Temp.	-10 ~ 55 °C w/ 0.7m/s Airflow		
	Storage Temp.	-40 ~ 85 °C (-40~185 °F)		
	Relative Humidity	40 °C @ 95%, Non-Condensing		
<b>Physical Characteristics</b>	Dimensions	290.35* 132.38* 186 mm (W* H* D)		
	Net Weight	4.55 KG		
<b>Regulation</b>	EMC	CE/FCC Class B, CCC		
	Safety	CE-LVD, RoHS, CCC		



The actual appearance and dimensions are subject to the final configuration



### Ordering Information

SO-DIMM Socket	M.2 2280 M-key Slot	mSATA3.0 Slot	SATA3.0 Connector	PCIe/PCI Expansion Slot	Full Size Mini-PCIe	M.2 2230 E-key Slot	Isolated RS232/ RS485	Non-Isolated RS232	RS232 Header	GbE LAN		
2	1	1	4	2	1	1	4	1	1	3		
USB3.0	USB2.0	Internal USB2.0	HDMI Or DP	VGA	MIC	SPK	External SIM Card Slot	PS/2	Remote Switch	8-bit GPIO	Auto-On Switch	Power Supply
8	2	1	1	1	1	1	1	1	1	1	1	DC 9-36V

### Packing list

Default Items	Qty
IBOX-602-5C3L-2P Unit	1
AC-to-DC Adapter	1
Power cable 3-pin 150cm	1

### Options for default items

Optional Items	Qty
Power cable 3-pin 150cm, USA type	-
Power cable 3-pin 150cm, EU type	-
Power cable 3-pin 150cm, UK type	-
Swappable hard-drive bracket kit	-

## Processors Info & Available List

CPU	Code Name	Total Cores	Total Threads	Max Turbo Frequency	Base Frequency	Cache	TDP	Memory Types	Integrated Graphics
Intel® Core™ I3-6100	Skylake	2	4	-	3.70 GHz	3 MB Intel® Smart Cache	51 W	DDR4	Intel® HD Graphics 530
Intel® Core™ I5-6500	Skylake	4	4	3.60 GHz	3.20 GHz	6 MB Intel® Smart Cache	65 W	DDR4	Intel® HD Graphics 530
Intel® Core™ I7-6700	Skylake	4	8	4.00 GHz	3.40 GHz	8 MB Intel® Smart Cache	65 W	DDR4	Intel® HD Graphics 530
Intel® Celeron® G4900	Coffee Lake	2	2	-	3.10 GHz	2 MB Intel® Smart Cache	54 W	DDR4	Intel® UHD Graphics 610
Intel® Core™ I3-7100	Kaby Lake	2	4	-	3.90 GHz	3 MB Intel® Smart Cache	51 W	DDR4	Intel® HD Graphics 630
Intel® Core™ I5-7400	Kaby Lake	2	4	3.50 GHz	3.00 GHz	6 MB Intel® Smart Cache	65 W	DDR4	Intel® HD Graphics 630
Intel® Core™ I7-7700	Kaby Lake	4	8	4.20 GHz	3.60 GHz	8 MB Intel® Smart Cache	65 W	DDR4	Intel® HD Graphics 630
Intel® Core™ I3-8100	Coffee Lake	4	4	-	3.60 GHz	6 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I5-8500	Coffee Lake	6	6	4.10 GHz	3.00 GHz	9 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I7-8700	Coffee Lake	6	12	4.60 GHz	3.20 GHz	12 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I3-9300	Coffee Lake	4	4	4.30 GHz	3.70 GHz	8 MB Intel® Smart Cache	62 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I5-9400	Coffee Lake	6	6	4.10 GHz	2.90 GHz	9 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I7-9700	Coffee Lake	8	8	4.70 GHz	3.00 GHz	12 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630
Intel® Core™ I9-9900	Coffee Lake	8	16	5.00 GHz	3.10 GHz	16 MB Intel® Smart Cache	65 W	DDR4	Intel® UHD Graphics 630

All products and company name listed are trademarks or trade names of their respective companies.

!! Note: For more interface configuration or available processors, please consult the sales.

## Optional accessories or internal modules for unit

Optional Items	Max Qty	Description
Isolated RS-232	1	DB9 or Phoenix Terminal connector, connected by header
Non-Isolated RS-232	1	DB9 or Phoenix Terminal connector, connected by header
Non-Isolated RS-422	1	DB9 or Phoenix Terminal connector, connected by header with a transform module
Non-Isolated RS-485	1	DB9 or Phoenix Terminal connector, connected by header with a transform module
Isolated 8-bit GPIO, 9-24V	1	Phoenix Terminal connector, connected by header
Isolated 8-bit GPIO with current loading, 9-26V	1	Digital signal, Phoenix Terminal connector, connected by non-standard M.2 interface
Isolated 15-bit GPIO, 0-5V	1	Digital signal, Phoenix Terminal connector, connected by non-standard M.2 interface
Isolated 15-bit GPIO with 7-in & 8-out, 12-24V	1	Digital signal, Phoenix Terminal connector, connected by non-standard M.2 interface
4G Module	1	Connected by Mini-PCIe interface
WiFi Module without AP mode	1	Connected by Mini-PCIe interface, M.2 interface or internal USB interface
WiFi Module with AP mode	1	Connected by Mini-PCIe interface
Dual channel CAN-Bus Module	2	Connected by Mini-PCIe or M.2 interface
Dual/Quad channel CAN-Bus Module	1	Connected by PCIe Interface
Dual GbE PoE LAN Module	1	Connected by Mini-PCIe Interface
Quad GbE PoE LAN Module	2	Connected by PCIe Interface

!! Note: As this product has expansion slots, please consult sales for the specific maximum number of expandable interfaces.